

Quotation

for

Technometal Orfanidis E.E.

DMU 50



Highlights

- By CELOS simple operation and holistic Integration in the business organization*
- Optimum flexibility Variable table options from rigid to swivel rotary table with digital drives for automatic 5-axis machining
- _ **Optimum space economy** Excellent accessibility to the work area, good chip disposal and steeply slanted walls, large working area in relation to small machine size
- _ Digital drives and direct measuring systems (optional) guarantee highest precision and top surfaces
- Mounting of tool magazine parallel to production time
- Powerful motor spindle with up to 18,000 rpm (optional)

^{*}Only in conjunction with CNC control CELOS with Siemens



Investment summary

S-A3172	DMU 50 New DMG MORI Design	
S-B3256	Control CELOS with Siemens 840D sl Operate	
S-T3013 S-C3042 S-D3048 S-K3130 S-N3029 S-N3332	Packages DMU 50 '21 COMPLETE, consisting of: Swivel Rotary Table, simultaneous Tool magazine 30 po SK40 vertical chain Direct measuring systems X/Y/Z Air seal for linear measuring systems Package Price BENEFIT of 75%	
S-K3272 S-K3367 S-N3004 S-N3018	Cooling media / chip removal Swarf conveyor Internal coolant supply 40bar/600l Spray gun for swarf removal Coolant-air blast change-over	
S-K3201	Automation Signal lamp 4 colour	
S-H3095	Options for CELOS with Siemens / Siemens Manual control panel	
S-D/GB	Screen Text Language Screen text german/english	
SK001 SK002	Special constructions S-K3527 Measuring kit Renishaw S-K3494 Preparation 3D quickSET	
D-CO100 D-CO102 D-CO101	DMG MORI Connectivity IoTconnector Machine Data Connector NETservice	
D-MO001	DMG MORI Monitoring Messenger V4	
D-MT001	DMG MORI Maintenance Service Agent	
S-P3124 S-P3076 S-P3013 S-O3134	Packing / Transport / Installation Packing base/cover DMU 50 Packing base/cover swarf conveyor Packing base/cover Internal coolant supply Dispatch basic machine	
SK003 SK004	Special constructions services Installation at customer premises 3 days training at customer premises	

^{*} further description see attachment



DECKEL MAHO DMU 50

Basic machine

S-A3172*	Universal Milling Machine DMU 50 New DMG MORI Design Traverse range X/Y/Z 500/450/400 mm / 19.6/17.7/15.7 in 30 m/min / 98,4 ft/min Rapid feed Speed range 20 to 14.000 r.p.m InLine spindle with 20,3/14,5 kW / 27,2/19,4 hp (40/100%ED) Tool taper ISO40 DIN 69871 Cabin-guarding	1	
Control			
S-B3256*	CELOS with Siemens 840D sl Operate includes 21,5" ERGOline® Control with Multi-Touch-Screen.	1	
Packages			
S-T3013	DMU 50 '21 COMPLETE, consisting of:	1	
S-C3042*	Swivel Rotary Table for simultaneous machining Clamping surface dia. 630 x 500mm / 24.8 x 19.6 in swivel range -5 to +110°, rotary axis 360° including direct measuring system for B- and C-axis and working plane transformation Not available with NC-Divider EA 410!	1	
S-D3048*	Tool magazine 30 places SK40 Vertical chain with double gripper incl. set up station for tool loading	1	
S-K3130	Direct measuring systems X,Y,Z axes	1	
S-N3029	Air purge for linear measuring systems X,Y,Z	1	
S-N3332	Package Price BENEFIT of 75%	1	
Cooling media / chip removal			
S-K3272	Swarf conveyor, scraper type	1	
	• • • • • • • • • • • • • • • • • • • •		

DMG MORI

S-K3367*	Internal coolant supply (ICS) with paper type filter, 40 bar/23 l/min / 600-l tank 580 psi/6 gallon/min /160 gallon incl. cabin roof,rotary joint inspindle, rotating clear-view window (not available with option 2nd cabin door)	1
S-N3004	Spray gun for swarf removal	1
S-N3018	Coolant - air-blast changeover external, switchable via M-Function	1
Automation	1	
S-K3201	Signal lamp 4-colour Red: general error Yellow: intervention necessary Green: automatic mode Blue: set-up mode	1
Options for	CELOS with Siemens / Siemens	
S-H3095	Electronic handwheel	1
Screen Tex	t Language	
S-D/GB	Screen text german/english	1
Special con	structions	
SK001	S-K3527 Measuring kit Renishaw touch probe PP40 optical with tool taper TS27R contact tool setting probe for tool length and tool diameter measurement	1
SK002	S-K3494 Machine preparation for use of the 3D quickSET Toolkit. included is the Softwareoption for 3D quickSET for one machine. 5 axis machine configurations (only with option touch probe)	1
DMG MORI Connectivity		
D-CO100*	IoTconnector The IoTconnector allows the use of online services of DMG MORI (e.g. NETservice)	1
D-CO102*	Machine Data Connector (MDC) Uniform machine data interface.	1
D-CO101*	NET service Qualified support by Internet-based remote diagnostics	1

1

1

1



D-MO001*	Messenger V4 Clear presentation of the machine live status.			
DMG MORI	Maintenance			
D-MT001*	Service Agent Overview of all maintenance work on the machine			
Packing / Transport / Installation				
S-P3124	Packaging base with foil DMU 50			
S-P3076	Packaging base with foil swarf conveyor			

Special constructions services

S-P3013

S-O3134

DMG MORI Monitoring

SK003	Installation at customer premises	1
SK004	3 days training at customer premises	1

Packaging base with foil ICS

Dispatch basic machine